



SPECIFICATIONS
AD SERIES
 DUCTLESS RANGE HOODS

Advantage Series Ductless Range Hood
 120 Volts, 0.7 amps, 60 hz.

• **Dimensions**

Overall bottom projection - 18 1/2"
 Overall top projection - 12"
 Height - 6". Available widths: 21", 24", 30" & 36"

• **Hood Body**

23 gauge cold rolled steel, auto welded, coated with a baked enamel finish.

• **Motor**

2 speed, single coil, thermally protected, permanently lubricated.
 Rated 120 volts, 60 hz., 0.7 amps. Complete with 105°C lead wires.

• **Lighting**

Single 60 watt cook light capacity (bulb not included).

• **Ducting Options**


Ductless - combination grease/charcoal filter included.
 (Model RF55)

• **Fan Blade**


One piece polymeric, electronically balanced blade.
 6 1/8" diameter with 3 paddles.

• **Electrical connection**

Hood top - 7/8" electrical knockout.
 Hood back - 7/8" electrical knockout.



AD SERIES



• **Filters**

UL rated, class 2 filter.
 Combo Grease/Charcoal: RF55 - 8 7/8"x10 3/8" (included).

• **Available Finishes**

White, Biscuit, Almond, Black & Stainless Steel.

PROJECT							ARCHITECT		
LOCATION							ENGINEER		
CONTRACTOR							SUBMITTED BY		DATE
FAN NUMBER	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS



U.S.: 820 Lincoln Avenue
 West Chester, Pennsylvania 19380-4466
 Tel: (610) 692-7400 • 877-304-3785
 Fax: (610) 696-8048

Canada: 8 Edvac Drive
 Brampton, Ontario L6S 5P2
 Tel: (905) 456-2033
 Fax: (905) 456-1015