




SPECIFICATIONS  
**BFQ75**  
 EXHAUST FANS

**70 CFM/1.5 SONES @ 0.10" WG.**  
**HVI CERTIFIED 120 Volts, 0.25 amps, 60 hz.**

- **Grill**  
 White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - 10" x 10".
- **Blower Wheel**  
 One piece polymeric wheel 5<sup>1</sup>/<sub>8</sub>" diameter, 2<sup>3</sup>/<sub>8</sub>" wide, with 48 fins.
- **Motor**  
 Heavy duty, permanently split capacitor, plug-in, 4 pole motor, life time lubrication, thermally protected, suitable for continuous operation. Rated 120 volts, 60 hz., 0.25 amps.
- **Fan Housing**  
 Flame retardant ABS, 0.110" thick, dimensions 8<sup>1</sup>/<sub>2</sub>" x 9<sup>1</sup>/<sub>16</sub>" x 4<sup>3</sup>/<sub>4</sub>".
- **Duct Collar**  
 Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.
- **Ventilating Area**  
 For bathrooms up to 65 sq. ft. For other rooms up to 85 sq. ft.
- **Single Pack Shipping Info**  
 Box Dim: 11" x 12" x 6"  
 UPC: 0-8316227501-1  
 Shipping Weight: 5<sup>1</sup>/<sub>4</sub> lbs.



Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.



- **Unit Mounting**  
 Rated for ceilings insulated to R-40. Designed to mount in ceilings with at least 6" of clearance. The unit is mounted directly to the joist using a separate lock-in bracket (included with unit). The housing will mount through drywall thickness up to 3/4", with a rough-in opening of 8<sup>1</sup>/<sub>2</sub>" x 9<sup>1</sup>/<sub>16</sub>".

PERFORMANCE												
	Static Pressure (inches of w.g.)								Sones @ .1 SP	Sones @ .25 SP	Fan Speed RPM	Power Watts
	0	0.05	0.1	0.125	0.15	0.2	0.25	0.3				
<b>Air Flow - CFM</b>	79	74	70	68	66	62	57	50	1.5	2.0	1300	30

<b>PROJECT</b>					<b>ARCHITECT</b>					
<b>LOCATION</b>					<b>ENGINEER</b>					
<b>CONTRACTOR</b>					<b>SUBMITTED BY</b>				<b>DATE</b>	
FAN NUMBER	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS	



**U.S.:** 820 Lincoln Avenue  
 West Chester, Pennsylvania 19380-4466  
 Tel: (610) 692-7400 • 877-304-3785  
 Fax: (610) 696-8048

**Canada:** 8 Edvac Drive  
 Brampton, Ontario L6S 5P2  
 Tel: (905) 456-2033  
 Fax: (905) 456-1015