

### **Specifications**

F.O.B Sedalia, Missouri 65301



#### **OPTIONS:**

- Safety pilots
- ☐ Stainless steel liner FMOD-SS-LINER
- ☐ Stainless steel feet -SS-FEET
- Adapter plates 31, 32, 33
- ☐ Telescope covers 546, 548
- ☐ Spillage pans 576, 676
- Stainless steel cutting board in lieu of poly
- ☐ Hardwood cutting board in lieu of poly
- ☐ Drop type brackets for cutting board
- ☐ Standard serving shelf 656-x
- ☐ Deluxe serving shelf 956-x
- ☐ Standard buffet shelf 63x
- ☐ Deluxe buffet shelf 83x
- ☐ 3-bar tray slide 3BTS-x
- ☐ Stainless steel dish shelf under cutting board 441S-x
- Solid stainless tray slides SOLID-FX/HD

# Approval Stamp(s):

PRODUCT INFORMATION:	
PROJECT:	
ITEM:	
QUANTITY:	
MODEL:	
Aerohot™ Steamtables	
Hot Food Units - Gas	

□ 302
□ 303
□ 304
□ 4 top openings
□ 305
□ 5 top openings

#### TOP:

- 20 gauge, 300 Series stainless steel
- Die-stamped openings 12" x 20"
- Poly carving board 7"W x 1/2" thick with 18 gauge stainless steel support base and die-stamped brackets

#### **HEAT COMPARTMENTS:**

- Die-formed galvanized steel 8" deep
- Insulated on all four sides and bottom with fiberglass

#### **BODY AND INTERIOR SHELF:**

- 20 gauge, 430 Series stainless steel body
- 20 gauge, 430 Series stainless steel undershelf
- 430 Series stainless steel tubular legs with adjustable plastic feet

#### **CONTROLS**

- Natural or Propane, as specified
- Galvanized steel radiation plate in each compartment
- Gas pressure regulator furnished in each unit
- Burners controlled by individual adjustable valves

#### AGENCY LISTINGS:






DUKE MANUFACTURING CO. 2305 N. Broadway St. Louis, MO 63102

800.735.3853 Toll Free 314.231.5074 Fax www.dukemfg.com

#### SHORT FORM SPECIFICATIONS:

Aerohot™ Steamtables - Hot Food - Gas. Top shall be heavy gauge, 300 Series stainless steel with body, undershelf and legs formed of heavy gauge 430 Series stainless steel. Top shall have die-stamped openings, measuring 12" x 20". Units to be furnished with poly carving board measuring 7" x 1/2" thick with 18 gauge stainless steel support base and diestamped brackets. Die-formed heat compartments, 8" galvanized liner, each insulated on all four (4) sides and bottom with 1" thick fiberglass or equal, with thermal conductivity of 0.27 or less. Each compartment shall have individual burner rated at 2500 BTU for propane or 1,000 BTU for natural. Burners controlled by adjustable valve. Galvanized radiation plate in each compartment and gas pressure regulator to be furnished. Unit shipped semi-knocked down.

## aerohot




#### MODEL: Aerohot™ Steamtables Hot Food Units - Gas

□ 302
□ 303
□ 304
□ 4 top openings
□ 305
□ 5 top openings

Freight Class: 85


LEGEND	
I- GAS CONNECTION	

**TOP VIEW** 



**FRONT VIEW** 





**RIGHT SIDE VIEW** 

#### **DIMENSIONS:**

	Length		Width		Height		Тор	Cube ft.	Weight	
Model	in.	cm	in.	cm	in.	cm	Openings	Crated	lbs.	kg
302	30-3/8	77.2	22-7/16	57.1	34	86.4	2	23.4	92	41.8
303	44-3/8	112.8	22-7/16	57.1	34	86.4	3	32.5	109	49.6
304	58-3/8	148.3	22-7/16	57.1	34	86.4	4	41.5	139	63.2
305	72-3/8	183.9	22-7/16	57.1	34	86.4	5	50.5	166	75.5

POWER SUPPLY: High altitude orifice available - specify elevation. SPECIFY NATURAL OR PROPANE.

Model	# Burners	Total BTU
302	2	5,000
303	3	7,500
304	4	10,000
305	5	12,500

NOTE: No combustible materials should be stored on bottom shelf. NOT AVAILABLE IN PORTABLE MODELS



DUKE MANUFACTURING CO. 2305 N. Broadway St. Louis, MO 63102

800.735.3853 Toll Free 800.231.1130 In Missouri 314.231.5074 Fax www.dukemfg.com