GLOBE FOOD EQUIPMENT COMPANY

10

Quart Mixer



Standard Features

- Powerful 1/3 HP custom built motor
- Three fixed speeds
- Gear-driven, high torque transmission
- Heat-treated hardened steel alloy gears
 and shafts
- Permanently lubricated transmission
- Thermal overload protection
- Rigid cast iron body
- Removable stainless steel bowl guard with built in ingredient chute
- NSF approved enamel gray paint
- Front mounted controls
- 15 minute timer
- Industry standard #12 attachment hub
- · Safety interlocked bowl guard and bowl lift
- Non-slip rubber feet
- 6 foot cord and ground plug

Standard Accessories

- 10 quart stainless steel bowl
- Flat beater (aluminum)
- · Stainless steel wire whip
- Spiral dough hook (aluminum)



Globe

SP10 10 Quart Mixer

Model □ SP10 - 10 Quart Mixer

Built into each mixer is the quality of workmanship and design synonymous with Globe.



Optional Attachments/Accessories

- □ Slicer/shredder/grater for #12 hub
- □ Meat grinder for #12 hub
- □ Flat beater (stainless steel)
- Spiral dough hook (stainless steel)
- □ Mixer table with undershelf

Standard Warranty

• Two-years parts and one-year labor

Featuring a Removable Bowl Guard



- High-quality stainless steel removable bowl guard
- Interlocking guard easy to attach and remove for easy cleaning
- Dish machine safe

Approved By:_____

Date:

GLOBE FOOD EQUIPMENT COMPANY

2153 Dryden Rd. Dayton, OH 45439 Phone: 937-299-5493 Phone: 800-347-5423 Fax: 937-299-4147 SP10

www.globeslicers.com



10 Quart Mixer

Motor: 1/3 HP, grease packed ball bearing, air cooled, 115/60/1, 8 amps. Thermal overload protection (automatic reset).

Finish: NSF approved enamel gray paint.

Capacity: 10 quart (9 liter) bowl.

Transmission: Fixed speed transmission is made of heat treated, hardened alloy, precision milled gears that operate the planetary action and provide high torque mixing power. The gears are packed in a long lasting grease, and all shafts are mounted in ball bearings.

Removable Bowl Guard:

Removable stainless steel bowl guard made of high-quality stainless steel. Interlocking guard is easy to attach and remove for easy cleaning in a sink or dishwasher. When quard is open or not properly installed, the mixer will not operate.

Safety Interlocks: The bowl guard and bowl lift lever are interlocked. The mixer will automatically shut down when the guard is opened or the bowl is lowered.

7.3 (18.5)

15 (38.1)

Agitator Speeds (RPMs):

Low	104
Intermediate	194
High	353

Specifications

Attachment Speeds (RPMs): I ow 50

LOW	59	
Intermediate	110	
High	201	
riigii	201	

Standard Equipment: Standard equipment includes a 10 quart #304 series stainless steel bowl, aluminum spiral dough hook, stainless steel wire whip, aluminum flat beater, removable stainless steel bowl guard with built in ingredient chute, 15 minute timer, and #12 attachment hub. A sturdy hand lever on the body column raises and lowers the bowl as well as locking in place at the top and bottom positions.

Cord: 6 ft. flexible three wire cord and ground plug.

Dimensions:

21.25 (54)


16 (40.6)

30.5 (77.47)

Foot Print = 15" x 16" (38.1cm x 40.6 cm) Overall Length = 21.25'' (40 cm) Overall Width = 16.3" (41 cm) Overall Height = 30.5'' (77.5 cm)

Shipping Information:

Freight Class: 85 Net Weight: 132 lbs. (60 kg) (pallet). The weight and dimensions may vary from shipment to shipment.





XXBEAT-10SS Stainless Steel Flat Beater XXHOOK-10SS Stainless Steel Spiral Dough Hook

XTABLE Mixer Table with undershelf (stainless steel top with galvanized steel undershelf and legs) 30"W x 24"D x 24"H (76.2 cm x 61 cm x 61 cm)

Optional Attachments:

XMCA-SS Meat Grinder Assembly (Polished stainless steel cylinder, worm gear, ring, and pan. Includes knife, 3/16" plate, stainless steel pan, and pusher.) Chopper Plate Sizes Available:

opper r late c	51200710	unubic.
CP02-12	1/16"	(2mm)
CP04-12	5/32"	(4mm)
CP05-12	3/16"	(5mm)
CP06-12	1/4"	(6mm)
CP08-12	5/16"	(8mm)
CP10-12	3/8"	(10mm)
CP12-12	1/2"	(12mm)
CP14-12	9/16"	(14mm)
CP16-12	5/8"	(16mm)
CP18-12	11/1"	(18mm)
CP00-12	Stuffing	Plate
XST12 1/2"	stuffing	tube (sheep)
XST34 3/4"	stuffing	tube (hog)

XVSGH 9" Slicer/Shredder/Grater Housing Only (no plates includedmust select from plates below)

XASP Adjustable slicing plate XPH Plate holder - *only 1 required

Shredding/Grating Plates:

XSP332*	3/32"	(2.3mm)
XSP316*	3/16"	(4.7mm)
XSP14*	1/4"	(6.3mm)
XSP516*	5/16"	(7.9mm)
XSP12*	1/2"	(12.7mm)
XGP*	Grating plate	

Printed in U.S.A. 04-2010 • Rev.1 3-2012



GLOBE FOOD EQUIPMENT COMPANY www.globeslicers.com

UNIT: INCHES (CM)

16 x 3 1/2" Long Tap

Dayton, OH 45439 Phone: 937-299-5493 Phone: 800-347-5423 Fax: 937-299-4147

2153 Dryden Rd.

Specifications are subject to change without notice.

SP10