

Job: _____

Item No.: _____

Model No.: **PB14**

BOWL CUTTER WITH 14" BOWL

Standard Equipment: Bowl cutter, 14" diameter stainless steel bowl 24 rpm, twin stainless steel knives 3,500 cuts/min, pull/push on-off, bowl cover interlock, polished & anodized aluminum construction, 1/2 hp motor, 5' cord & plug. Tamper-resistant, nonremovable screws. Non-removable tamper-proof knobs and handles.

Features & Benefits:

- Perfect for pulled pork, parsley, root vegetables, meats, cheeses, breads, spreads, dips and salads
- 1 HP motor
- 14" stainless steel bowl rotates at 24 rpm
- Cutlery stainless steel twin blades make 3,500 cuts per minute
- Polished and anodized aluminum body
- Simple operation: Pull / push on and off switch with illuminated indicator lamp when unit is on.
- Bowl cover interlock prevents unit from running when cover is in improper position
- Bowl sensing switch prevents operation without the bowl
- Cord and plug

Standard Accessories

- 14" 304 stainless steel bowl
- Twin cutlery grade knives

Optional Upgrades

- Plastic cover



Warranty:

The PB14 carries a one-year, on-site parts and labor warranty against any flaws in materials and workmanship. This period begins date of purchase and, provided the unit is used in accordance with instructions, is in full effect for one year from that date. Any work performed under this warranty must be performed between the hours of 8:00 a.m. and 5:00 p.m. local time, Monday

through Friday. Prisonbilt will not pay for overtime charges for work performed other than during normal business hours. Damage incurred in transit or from installation error, accident, alteration or misuse is not covered. Prisonbilt shall not be liable for any consequential, compensatory, incidental, or special damages. Contact the Prisonbilt service department for any warranty claims.

PRISONBILT

4900 W. Electric Avenue • West Milwaukee, WI 53219
phone (414) 902-6680 • fax (414) 902-6446
www.prisonbilt.com

Job: _____

Item No.: _____

Model No.: **PB14**

Construction Specifications:

- **Electrical:** 115/60/1. Other voltages may be available.
- **Motor:** ½ HP capacitor start with starting relay. Speed 1725 RPM, ball bearing shaft.
- **Drive:** Knife shaft, ball bearing mounted, driven at 1725 RPM by a 8-ribbed poly "V" belt.
- **Knife Blades:** Cutlery stainless steel, 3500 cuts per minute.
- **Bowl:** 14" (356mm) diameter, polished, die drawn, 304 stainless steel, 1:1.6 ratio driven at 24 RPM with "O" ring belt pulley reduction with 45:1 worm gear reduction.
- **Housing & Bowl Cover:** Cast aluminum. Polished and anodized.
- **Switch:** DPST pull / push on-off.
- **Circuit Breaker:** 6.0 amp manual reset.
- **Cord and Plug:** 3-wire, 16 gauge, 5ft (1524mm) long SJT cord with 3 prong-molded plug.
- **Safety Features:** Bowl cover interlock prevents running when cover is in improper position. Bowl sensing switch prevents operating without bowl.



BOWL CUTTER DIMENSIONS:

- A) Height: 16" (406 mm)
- B) Width: 27" (686 mm)
- C) Length: 18" (457 mm)

SHIPPING INFORMATION:

- Freight Class: 85
- Net Weight: 93 lbs (42 kg)
- Shipping Weight: 99 lbs (45 kg)

SHIPPING BOX DIMENSIONS:

- Height: 17" (430 mm)
- Width: 23" (580 mm)
- Length: 31" (790 mm)

Item Number	Description	Overall Size			Case Weight	
		L	W	H	Lbs	(Kg)
PB14	14" Diameter	18" (457 mm)	27" (686 mm)	16" (406 mm)	99	(45)

PRISONBILT

4900 W. Electric Avenue • West Milwaukee, WI 53219
 phone (414) 902-6680 • fax (414) 902-6446
 www.prisonbilt.com