

Job: \_\_\_\_\_

Item No.: \_\_\_\_\_

Model No.: **PBM100**

## MANUAL SLICER

Robust construction and superb engineering combine to produce a manual slicer perfect for the heavy slicing needs of a correctional facility. The slicer uses an oversized, 13" German-made, high carbon chrome-plated blade that slices from wafer thin up to 0.9". The 13" blade is fully protected, even during cleaning! Ultra-smooth anodized aluminum surfaces provide superior glide that reduces operator fatigue and simplifies cleaning. Ideal for high-volume operations, the durable polished aluminum will maintain its matte silver sheen for years to come. Anodized aluminum remote sharpener is easy to use, mounts in seconds, and can be secured when not in use. Carriage tilts away from unit for quick and easy cleaning. Extra large feed grip disassembles easily for thorough cleaning. Captive blade cover knob stays attached to unit, no small pieces to lose! Safety features include zero blade exposure during cleaning, carriage system interlock and no volt release.



### Features & Benefits:

- 13" Blade
- 1/2 HP Blade Motor
- Tamper-proof screws on bottom cover protect internal components
- HD Heyco at cord attachment to slicer body
- Nonremovable, tamper-proof carriage and blade cover knob
- Hygienic remote sharpener mounts in seconds
- All other knobs and handles are drilled, pinned, and lock tightened to be nonremovable
- Sanitary polished and anodized aluminum construction
- Carriage tilts back for easy cleaning
- Sealed on/off switch illuminated when unit is running

#### Standard Accessories

- Remote sharpener
- Extra large feed grip
- Permanent blade edge guard
- Lift lever for cleaning

#### Optional Upgrades

- Slicer cover
- Vegetable chute attachment

### Warranty:

The PBM100 carries a one-year, on-site parts and labor warranty against any flaws in materials and workmanship. This period begins date of purchase and, provided the unit is used in accordance with instructions, is in full effect for one year from that date. Any work performed under this warranty must be performed between the hours of 8:00 a.m. and 5:00 p.m. local time, Monday

through Friday. Prisonbilt will not pay for overtime charges for work performed other than during normal business hours. Damage incurred in transit or from installation error, accident, alteration or misuse is not covered. Prisonbilt shall not be liable for any consequential, compensatory, incidental, or special damages. Contact the Prisonbilt service department for any warranty claims.

### PRISONBILT

4900 W. Electric Avenue • West Milwaukee, WI 53219  
phone (414) 902-6680 • fax (414) 902-6446  
www.prisonbilt.com

Job: \_\_\_\_\_

Item No.: \_\_\_\_\_

Model No.: **PBM100**

**Construction Specifications:**

- **Slice Thickness:** Infinitely variable, from 0 to .9" (0 to 23 mm)
- **Max Product Size:** Carriage will fit product up to 10" in width or 8" in diameter
- **Blade:** 13" (33 cm) diameter German made, hollow-ground, chrome-plated, high-carbon steel.
- **Motor:** 1/2 hp; 2.5 amp draw
- **Electrical:** 120/60/1-phase. Consult factory for special voltages. Power on indicator light
- **Controls:** Manual Operation. Membrane covered, color-coded ON and OFF switch. Slice thickness control.
- **Construction:** Ultra-smooth, polished anodized aluminum chassis, support and feed carriages, gauge plate, blade guard, remnant holder.
- **Electrical Cord:** Six foot, three-wire power supply cord and plug. furnished on export models.
- **Hygiene/Maintenance:** Removable blade guard and remnant holder. Rear product deflector swivels to allow easy access for cleaning. Separate sharpener mounts in seconds.
- **Knife Ring Guard:** Permanently mounted knife ring guard protects the non-slicing portion of the knife. With the gauge plate completely closed, the slicer and blade can be cleaned with zero blade exposure.
- **No Voltage Release:** Prevents inadvertent reactivation of slicer in the event of power interruption. Operator must restart the slicer.
- **Indicator Light:** Readily visible light illuminates when knife is rotating.
- **Tilting Carriage System:** With thickness dial set to "0", carriage tilts back easily for cleaning. Carriage system interlock does not allow gauge plate to be opened with carriage tilted for cleaning.



**SLICER DIMENSIONS:**

- A) Height: 23" (584mm)
- B) Width: 23-1/2" (597mm)
- C) Depth: 22" (559mm)
- D) Width with carriage tilted: 36" (914mm)

**OPERATION AREA:**

- Width: 37" (940mm)
- Depth: 33" (838mm)

**SHIPPING INFORMATION:**

- Freight Class: 85
- Net Weight: 110 lbs (49.9 kg)
- Shipping Weight: 120 lbs (54.4 kg)

**SHIPPING BOX DIMENSIONS:**

- Height: 30" (762mm)
- Width: 39" (991mm)
- Length: 33" (838mm)

Item Number	Description	Dimensions (inches)			
		Height (A)	Width (B)	Length (C)	Width w/carriage tilted (D)
PBM100	Manual 13" Blade	23" (584)	23-1/2" (597)	22" (559)	36" (914)

**PRISONBILT**

4900 W. Electric Avenue • West Milwaukee, WI 53219  
 phone (414) 902-6680 • fax (414) 902-6446  
 www.prisonbilt.com