



Ready to use Vac-Norm external vacuum kit.



Cordless sealing bar in all models.

Vacuum packing machine SV-810 S - 220V / 60 Hz / 3~

Freestanding unit

- Two sealing bars of 33" and 21"

- Microprocessor: Control exact vacuum percentage in chamber.
- Plus vacuum: allows to program an extra vacuum time period once 99% vacuum has been reached.
- LEDs indicate each cycle stage whilst performing.
- A STOP key allows the interruption of the cycle at any stage, moving on to the next step.
- Easy to program. 10-program-memory.
- Softair with independent valve & gas flushing.
- Cordless sealing bar.
- Pump drying program, improving durability.
- Working hours counter display, informing when oil must be replaced.
- Ready to use Vac-Norm external vacuum kit.

Technical Data

Vacuum pump:	3500 cf/h
Sealing type:	Double
Sealing bar length:	33" + 21"
Electrical loading:	3 Hp
Vacuum pressure (maxi):	0.5 mbar

Chamber dimensions:	
-Width:	34"
-Depth:	24"
-Height:	8"

External dimensions:	
-Width:	39"
-Depth:	30"
-Height:	39"

Net weight:	551 lbs.
-------------	----------

ELECTRICAL SUPPLY:	220V / 60Hz /3~
--------------------	-----------------

COMPLETE WITH:

Insert plate set

OPTIONAL:

- Vac-Norm external vacuum kit
- Bag cutting kit
- Liquid insert plate set



UNE-EN ISO 9001

 SAMMIC, S.L. (Sociedad Unipersonal) □
 Basarte, 1 - 20720 AZKOITIA - www.sammic.com

 European directives
 2006/42/CE, 93/68 CEE,
 2006/95/CE

Norms