

Solid Door Freezers

Reach-In Bottom Mounts
New Maximum Series

Stainless Steel Interior and Exterior Digitally Controlled Uniform Temperature



MSF-23NM



MSF-49NM

FEATURES / BENEFITS

- DIGITAL TEMPERATURE CONTROL SYSTEM**
 Provides precise and constant temperature. This level of precision allows food products to remain fresh over an extended period of time.
- HIGH-TECH MONITOR**
 The unit will beep if the door has been opened for more than 30 seconds. The monitor digitally displays the present temperature and current status of the freezer. You can easily change the temperature by adjusting the thermostat.
- EFFICIENT REFRIGERATION SYSTEM**
 Turbo Air's solid door freezers are designed with over-sized and balanced (CFC Free R-404A) refrigeration systems. These include efficient evaporators and condensers for faster freezing and greater efficiency.
- AUTOMATIC EVAPORATOR FAN MOTOR DELAYS**
 Through stopping the evaporator fan when the freezer door opens, the circulation of hot, moist air into the freezer is prevented. This increases energy efficiency and lengthens the life of the compressor.
- STAINLESS STEEL CABINET CONSTRUCTION**
 The Turbo Air New Maximum model boasts a stainless steel interior and exterior (except the back). It guarantees the utmost in cleanliness and long product life. Unlike other companies' products, the sharp corners and edges have been rounded to reduce the risk of injury. The New Maximum can add a touch of style to the most refined setting.
- ADJUSTABLE, HEAVY DUTY, PE(POLYETHYLENE) COATED WIRE SHELVES**
- HIGH-DENSITY POLYURETHANE INSULATION**
 Entire cabinet structure and solid doors are formed-in-place using high density CFC free, polyurethane insulation.
- ERGONOMICALLY DESIGNED DOORS**
 Customers' fatigue fades away with easy grip handles and doors that open effortlessly. Self-closing and stay open door features make this the ultimate choice in customer convenience.
- MAGNETIC DOOR GASKETS**
 Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.
- BOTTOM MOUNT COMPRESSOR UNITS**
 Turbo Air's bottom mount compressor allows easier access for service and extra storage space above. In addition, the lower area provides a cooler and less greasy operating environment which results in reduced compressor running time.
- FREEZER HOLDS -10°F ~ 0°F FOR THE BEST IN FROZEN FOOD PRESERVATION**

Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Crated Weight	L D H
MSF-23NM	1	23	3	1/2	87	272	27 x 30³/₄ x 78¹/₄
MSF-49NM	2	49	6	3/4	105	445	54³/₈ x 30³/₄ x 78¹/₄

* Height does not include 6" for caster height.

MSF MODELS SPECIFICATIONS

ELECTRICAL DATA	MSF-23NM	MSF-49NM
Voltage ⓘ NEMA-5-15P	ⓘ 115/60/1	ⓘ 115/60/1
Amp	8.7A	10.5A
Compressor (HP)	1/2	3/4
Feed Wires (with ground)	3	3
Cord Length (ft.)	7	7
DIMENSIONAL DATA		
# of Doors	1	2
Cubic Feet	23	49
# of Racks Accepted	1	2
Length Overall (in)	27	54 ³ / ₈
Depth Overall (in)	30 ³ / ₄	30 ³ / ₄
Height Overall (in)	78 ¹ / ₄	78 ¹ / ₄
Interior Dimension (LxDxH)	23x24 ³ / ₄ x60 ³ / ₈	50 ¹ / ₂ x24 ³ / ₄ x60 ³ / ₈
Shelf Size	21 ⁵ / ₈ x23 ¹ / ₄	24 ³ / ₈ x23 ¹ / ₄
# of Shelves	3 ea	6 ea

*Design and specifications subject to change without notice.

- INCANDESCENT INTERIOR LIGHTING
- MINIMUM WATTAGE HEATER IN CABINET FRAME
- DOOR LOCKS
- SELF-CONTAINED SYSTEM
- 4" SWIVEL CASTERS
- SOLID AND STURDY GRILLE DESIGN
- LEGS AVAILABLE FOR ALL MODELS (OPTIONAL)
- TRAY RACK AVAILABLE (OPTIONAL)
All models accept full size door tray racks.
- REMOTE CABINETS AND CONDENSING UNITS AVAILABLE FOR ALL MODELS.

- **WARRANTY :** 1 Year Labor and Parts Warranty
Additional 4 Years Warranty on Compressor

(unit : inch)

