

# Half Solid Door Refrigerators

**Exceptional Quality 3 Years Parts and Labor Warranty**



**PRO-26-2R**



**PRO-50-4R**



**PRO-77-6R**

## ≡ FEATURES / BENEFITS ≡

- **DIGITAL TEMPERATURE CONTROL SYSTEM**  
Provides precise and constant temperature. This level of precision allows food products to remain fresh over an extended period of time.
- **HIGH-TECH MONITOR**  
The unit will beep if the door has been opened for more than 30 seconds. The monitor digitally displays the present temperature and current status of the refrigerator. You can easily change the temperature by adjusting the thermostat. Displays current status of the refrigerator.
- **EFFICIENT REFRIGERATION SYSTEM**  
Premiere's solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.
- **AUTOMATIC EVAPORATOR FAN MOTOR DELAYS**  
Through stopping the evaporator fan when the refrigerator door opens, the circulation of hot, moist air into the refrigerator is prevented. This increases energy efficiency and lengthens the life of the compressor.
- **STAINLESS STEEL CABINET CONSTRUCTION**  
The Turbo Air Premiere model boasts a stainless steel interior and exterior (except the back). It guarantees the utmost in cleanliness and long product life. Unlike other companies' products, the sharp corners and edges have been rounded to reduce the risk of injury. The Premiere can add a touch of style to the most refined setting.
- **STURDY, CLEAN STAINLESS SHELVING**  
Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Premiere series uniquely provides stainless shelving.
- **HIGH-DENSITY POLYURETHANE INSULATION**  
The entire cabinet structure and solid doors are formed-in-place using high density, CFC free polyurethane insulation.
- **ERGONOMICALLY DESIGNED DOORS**  
Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.
- **MAGNETIC DOOR GASKETS**  
Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.
- **HOT GAS CONDENSATE SYSTEM**  
Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but thoroughly prevents the overflow of condensate water.
- **TOP MOUNT COMPRESSOR UNITS**  
Premiere's top mount refrigeration system has positioned the evaporator out of the food zone to maximize capacity.
- **REFRIGERATOR HOLDS 33°F ~ 38°F FOR THE BEST IN FOOD PRESERVATION**

Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Weight	L D H
<b>PRO-26-2R</b>	<b>2</b>	<b>26</b>	<b>3</b>	<b>1/3</b>	<b>5.2</b>	<b>315</b>	<b>28<sup>3</sup>/<sub>4</sub> x 33<sup>7</sup>/<sub>8</sub> x 78</b>
<b>PRO-50-4R</b>	<b>4</b>	<b>50</b>	<b>6</b>	<b>1/2</b>	<b>9.1</b>	<b>484</b>	<b>51<sup>3</sup>/<sub>4</sub> x 33<sup>7</sup>/<sub>8</sub> x 78</b>
<b>PRO-77-6R</b>	<b>6</b>	<b>77</b>	<b>9</b>	<b>1/2</b>	<b>9.2</b>	<b>698</b>	<b>77<sup>3</sup>/<sub>4</sub> x 33<sup>7</sup>/<sub>8</sub> x 78</b>

\* Height does not include 5" caster height or 6" optional legs.

# PRO-R MODELS SPECIFICATIONS

ELECTRICAL DATA	PRO-26-2R	PRO-50-4R	PRO-77-6R
Voltage (NEMA-5-15P)	115/60/1	115/60/1	115/60/1
Amp	5.2 A	9.1 A	9.2 A
Compressor (HP)	1/3	1/2	1/2
Feed Wires (with ground)	3	3	3
Cord Length (ft.)	9	9	9
DIMENSIONAL DATA			
# of Doors	2	4	6
Cubic Feet	26	50	77
# of Racks Accepted	1	2	3
Length Overall (in)	28 <sup>3</sup> / <sub>4</sub>	51 <sup>3</sup> / <sub>4</sub>	77 <sup>3</sup> / <sub>4</sub>
Depth Overall (in)	33 <sup>7</sup> / <sub>8</sub>	33 <sup>7</sup> / <sub>8</sub>	33 <sup>7</sup> / <sub>8</sub>
Height Overall (in)	78	78	78
Interior Dimension (LxDxH)	24 <sup>3</sup> / <sub>4</sub> x27 <sup>5</sup> / <sub>8</sub> x60 <sup>5</sup> / <sub>8</sub>	47 <sup>3</sup> / <sub>4</sub> x27 <sup>5</sup> / <sub>8</sub> x60 <sup>5</sup> / <sub>8</sub>	73 <sup>7</sup> / <sub>8</sub> x27 <sup>5</sup> / <sub>8</sub> x60 <sup>5</sup> / <sub>8</sub>
Shelf Size	26 <sup>1</sup> / <sub>2</sub> x23 <sup>3</sup> / <sub>4</sub>	26 <sup>1</sup> / <sub>2</sub> x23 <sup>1</sup> / <sub>8</sub>	26 <sup>1</sup> / <sub>2</sub> x25 <sup>1</sup> / <sub>4</sub> 26 <sup>1</sup> / <sub>2</sub> x23 <sup>1</sup> / <sub>8</sub> 26 <sup>1</sup> / <sub>2</sub> x25 <sup>1</sup> / <sub>4</sub>
# of Shelves	3 ea	6 ea	9 ea

\*Design and specifications subject to change without notice.

- INCANDESCENT INTERIOR LIGHTING
- DOOR LOCKS
- SELF-CONTAINED SYSTEM
- 4" SWIVEL CASTERS
- SOLID AND STURDY GRILLE DESIGN
- LEGS AVAILABLE FOR ALL MODELS (OPTIONAL)
- TRAY RACK AVAILABLE (OPTIONAL)  
All models accept full size tray racks.
- REMOTE CABINETS AND CONDENSING UNITS AVAILABLE FOR ALL MODELS.

- **WARRANTY :** 3 Years Labor and Parts Warranty  
Additional 2 Years Warranty on Compressor

(unit : inch)

