



Project: _____
 Location: _____
 Item #: _____
 Quantity: _____

Extra-Wide Refrigerators

RS MODELS —

Stainless Steel Exterior
 Stainless Steel Interior

RS-1D-S7-EW
RS-2D-S7-EW
RS-3D-S7-EW

RSA MODELS —

Stainless Steel Exterior
 Aluminum Interior

RSA-1D-S7-EW
RSA-2D-S7-EW
RSA-3D-S7-EW

Half Door, Pass-Thru and Remote Models Available



RS-2D-S7-EW

Standard Features (all models)

- Digital Thermometer
- Adjustable Stainless Steel Legs
- Stainless Steel Case front, Door(s) and Sides
- Heavy-Duty Lifetime Cam Lift Hinges
- Adjustable Wire Shelves
- Lifetime Safety Grip Handle(s)
- Self-Closing Doors with Safety Stops
- Flush Mounted Automatic Interior Lighting
- Energy Saving Thermal Breaker strips
- Door Opening Accepts 12" x 20" and 18" x 26" pans
- Heavy-Duty Cylinder Locks
- One Piece Self Adjusting Magnetic Door Gasket(s)
- High Impact ABS Interior Door Liner(s)
- Environmentally Friendly R-134a Refrigerant
- Plasticized Fin Coil
- Non-Electric Condensate Evaporator
- Cord and Plug Attached on 115V Models
12 Amps or Less

Cabinet:

The cabinet front and doors are constructed of heavy gauge polished stainless steel to maintain an attractive appearance for years of heavy use. Foamed-in-place polyurethane insulation throughout the cabinet and doors ensures the ultimate in energy efficiency.

Doors:

The self-closing doors are securely mounted on rugged cam-lift hinges which have a lifetime guarantee. Each door has a heavy duty cylinder lock and self-adjusting magnetic gasket to prevent the cold air from escaping. Humidity control wires located around the door jamb prevent condensation from forming on the cabinet front and are concealed by a high impact, non-conductive thermal breaker strip. The interior door liner is constructed of durable ABS material which resists denting and scratching and is easy to clean. Each safety grip handle is guaranteed for life. Interior lighting is controlled by a switch mounted in the hinge.

Shelving:

The heavy-duty wire shelves are adjustable in one inch increments. A wide door opening allows the use of a variety of optional pan slide types for 12" x 20", 18" x 26" and 14" x 18" pans and trays.

Refrigeration System:

All components of the self-contained refrigeration system are mounted on top of the cabinet. The air circulating fans and the force convection cooling coil are contained in an insulated housing separate from the produce zone allowing for maximum food storage capacity. All condensate water is disposed of automatically by the energy efficient non-electric condensate evaporator, no plumbing required.

Optional Features and Accessories

- Dial Thermometer
- Two Half Doors in Place of One Full Length Door(s)
- Full and Half Sized Hinged Glass Doors with Cylinder Locks (consult factory)
- Change Door Swing
- Adjustable Stainless Steel Wire Shelves
- Stainless Steel Angle Pan Slides
- Zinc Plated Wire Pan Slides
- 5" Diameter Heavy-Duty Swivel Casters with Brakes
- Stainless Steel Case Back
- Fluorescent Lights (consult factory)
- Remote and Pass-Thru Models

Approvals:



Victory Refrigeration specification sheets are available online at www.victory-refrig.com

CHARACTERISTICS	ONE SECTION		TWO SECTION		THREE SECTION	
	Reach-In	Pass-Thru	Reach-In	Pass-Thru	Reach-In	Pass-Thru
Width, Overall	31-1/4	31-1/4	58-3/8	58-3/8	85-1/2	85-1/2
Depth, Overall (incl. handles)	34-1/2	36	34-1/2	36	35-7/8	39-3/8
Height, Overall (incl. adj. legs)	84	84	84	84	84	84
Depth, Door(s) Open 90°	58-1/4	85-1/2	58-1/4	85-1/2	60	87-5/8
Clear Door Width	22-3/4	22-3/4	22-3/4	22-3/4	22-1/2	22-1/2
Clear Full Door Height	54-5/8	54-5/8	54-5/8	54-5/8	55-1/4	55-1/4
Clear Half Door Height	25-1/4	25-1/4	25-1/4	25-1/4	25-3/8	25-3/8
Capacity Net (cubic feet)	24.4	26.2	52.0	55.6	79.6	84.9
No. of Full Doors	1	2	2	4	3	6
No. of Half Doors	2	4	4	8	6	12
No. of Shelves	3	3	6	6	9	9
Shelf Area (square feet)	19.1	19.1	38.2	38.2	57.3	57.3
Cabinet Voltage	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1
Feed Wires	2	2	2	2	2	2
Condensing Unit Voltage	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1
Condensing Unit Size (H.P.)	1/3	1/3	1/3	1/2	1/2	1/2
Total Amperes	9.8	10.0	10.7	11.0	10.6	13.1

Crated dim. & wts.	Ht.	Width	Depth	Cu. Ft.	Lbs.
One Section	84	36-1/2	44-3/4	82.2	430
Two Section	84	63-5/8	44-3/4	143.3	670
Three Section	84	90-3/4	44-3/4	204.4	1020

Approximate Pass-Thru Weights, add 15%


FOR REMOTE MODELS - Substitute an "R" in suffix. For Example: Model RS-1D-S7 (self contained) would be RS-1D-R7 remote refrigeration cabinet. Air circulating fans, expansion valve and plasticized coil are provided. Condensing units not supplied. The following units are recommended with 1/2" O.D. Suction Line, 1/4" O.D. Liquid Line.

REMOTE REFRIGERATION

	Cond. Unit	BTUH	Cabinet	Amps
One Section	1/3 H.P.	2540	115/60/1	4.9
Two Section	1/3 H.P.	2540	115/60/1	7.8
Three Section	1/2 H.P.	3800	115/60/1	8.5

For Remote Pass-Thru - Consult Factory

Dimensional Tolerance +/- 1/4" Metric Dimensions (MM)



Continuous product development may necessitate specification and design changes without notice.



Victory participates in the KCL CADalog, the most current symbols for foodservice designers worldwide. Symbols include standard equipment in plan, side, front and 3-D views, layered for FEDA/FCSI recommended guidelines.