## 18" SHALLOW-DEPTH SERIES

### **REFRIGERATOR**

#### **Perlick Features**

- 18" depth for design flexibility
- 32" height with leveling legs
- Front vented compressor
- Self-closing doors
- · Self contained, no plumbing required
- Whisper quiet 700 Btu high efficiency compressor
- Stainless steel interior standard
- Stainless steel exterior top and sides standard
- Two inch foamed-in-place insulation
- Interior light
- Adjustable full extension pull out vinyl coated shelves
- Multiple door finish options
- Low-E glass doors improve insulation and resist condensation on the glass
- Stainless steel ball bearing glides provide smooth movement of shelves
- Refrigerator temperature 33°-39° F

## **MODEL**

HD24RS









HD24RS (solid door)



HD24RS (glass door)





# **Size and Specifications**

18" Shallow-Depth Series Refrigerator







Job	
Area	
Item No.	
Model No.	

SERIES NO.		HD24RS Series Refrigerators
CABINET DIMENSIONS Depth - Inc	Length - Inches (mm)	23-7/8" (607)
	Depth - Inches (mm)	18-1/16" (550)
	Height - Inches (mm)	32" (812)
INTERIOR VOLUME -	CUBIC FOOT (M³)	3.810 ft³ (0.11)
SHELVING		2 FULL EXTENSION SHELVES
TEMPERATURE RANG	<b>RANGE</b> 33° - 39° F	
RUNNING LOAD - AMPS 2.3		2.3
CONDENSER UNIT H.P. 1		1/6 HP
SHIP WEIGHT Lbs. (kg)		185
INTERIOR	All stainless steel interior	
EXTERIOR	Stainless steel top and sides	
REFRIGERATION	R-134a capillary tube-type with hermetric compressor, front access condenser.	
ELECTRICAL	115V, 60Hz., phase 1, furnished with 3-prong NEMA 5-15 plug, 6 foot long cord	
PLUMBING	None required, moisture drains to self evaporating condensate pan.	
WARRANTY	1 year parts & labor; 5 year compressor	
OPTIONAL ACCESSORIES & MODIFICATIONS	Brass Hardware (classic, 12" and full length) or pull tab <b>Door finishes:</b> Black vinyl coated, stainless steel, customer choice of laminate, prepared for field lamination, glass door with black vinyl frame, glass door with stainless steel frame or glass door with laminated frame	



